

Subracks – EuropacPRO

REAR HORIZONTAL RAILS, TOP AND BOTTOM

ORDER INFORMATION

		For indirect backplane mounting with insulation strip		For direct backplane mounting		For direct fixing of connectors in accordance with EN 60603-2 (DIN 41612)							
 <p>06105074</p> <p>With HP markings from 28 HP, Al extrusion, anodised finish, conductive surface</p>		 <p>04400001</p> <p>"light" Type L-ST standard</p>  <p>04400002</p> <p>"heavy" Type H-ST standard</p>		 <p>04400002</p> <p>"light" Type L-VT + 3 mm</p>  <p>04400003</p> <p>"heavy" Type H-VT + 3 mm</p>		 <p>04400003</p> <p>"light" Type L-MZ with Z-rail</p>  <p>04400003</p> <p>"heavy" Type H-MZ with Z-rail</p>							
		 <p>06197010</p> <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p>		 <p>06197011</p> <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p>		 <p>06197011</p> <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p>		 <p>06197009</p> <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p>		 <p>06197014</p> <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p>		 <p>06197015</p> <p>Al extrusion, anodised surface, conductive contact surface, with printed HP markings</p>	
Usable length HP	Length mm	1 piece (SPQ 10) ¹⁾	1 piece (SPQ 10) ¹⁾	1 piece (SPQ 10) ¹⁾	1 piece (SPQ 10) ¹⁾	1 piece (SPQ 10) ¹⁾	1 piece (SPQ 10) ¹⁾						
20	106.68	34560-420	34560-520	34560-620	34560-720	34560-820	34560-920						
28	147.32	34560-428	34560-528	34560-628	34560-728	34560-828	34560-928						
40	208.28	34560-440	34560-540	34560-640	34560-740	34560-840	34560-940						
42	218.44	34560-442	34560-542	34560-642	34560-742	34560-842	34560-942						
63	325.12	34560-463	34560-563	34560-663	34560-763	34560-863	34560-963						
84	431.80	34560-484	34560-584	34560-684	34560-784	34560-884	34560-984						
–	1000	34560-401	34560-501	34560-601	34560-701	34560-801	–						
Screw, M4 x 14, PU 100 pieces, for fastening horizontal rail to side panel		24560-130	24560-130	24560-130	24560-130	24560-130	24560-130						
Screw, M4 x 10, required if guide rails are screwed to slot 1, PU 100 pieces		–	24560-155	–	24560-155	–	24560-155						
Perforated rail for connector mounting with insulation strip see page		6.36	6.36	–	–	–	–						
Z-rail for connector mounting without insulation strip see page		6.36	6.36	–	–	–	–						
Insulation strips see page		6.35	6.35	–	–	–	–						
Threaded inserts see page		6.35	6.35	6.35	6.35	6.35	6.35						

¹⁾ SPQ (standard pack quantity): Part number includes 1 piece, but delivery is exclusively made in standard pack quantity (SPQ); please order at least the SPQ quantity or a multiple
 "light": loading capacity up to approx. 7.5 kg; "heavy": loading capacity > 7.5 kg