




Subracks – EuropacPRO

GUIDE RAILS FOR PLUG-IN UNITS AND MODULES, ONE-PIECE, GROOVE WIDTH 2 MM AND 2.5 MM

ORDER INFORMATION

| | | | For plug-in units and frame type plug-in units standard type | | standard type, with DIN connector fixing |
|--|--------------------|--------------|--|--------------------------------|---|
| Assembly - can be clipped into Al extruded horizontal rails - can be clipped into 1.5 mm thick plates Storage temperature from -40 °C ... 130 °C | | |  | |  |
| | | | up to 220 mm length, PBT, UL 94 V-0; from 280 mm length, multi-piece, end piece PBT, UL 94 V-0, central section Al extrusion | PBT, UL 94 V-0 | PBT, UL 94 V-0, red, connector is clipped directly onto the guide rails; for euroboards only, 100 x 160 mm or 100 x 220 mm |
| Board length mm | Groove width mm | Colour mm | PU 10 pieces ²⁾ | 1 piece (SPQ 50) ¹⁾ | 1 pair (SPQ 10) ¹⁾ |
| 70 | 2 | red | – | 34579-230 | – |
| 70 | 2 | grey | – | 34579-231 | – |
| 160 | 2 | red | 24560-351 | 64560-001 | 64560-074 |
| 220 | 2 | red | 24560-353 | 64560-002 | 64560-075 |
| 280 | 2 | red | 24560-379 | – | – |
| 340 | 2 | red | 24560-380 | – | – |
| 160 | 2.5 | red | – | 64560-096 | – |
| 220 | 2.5 | red | – | 64560-098 | – |

Accessories

| | | | |
|--|------------------|---|------------------|
| Retention screw, PU 100 pieces; Torque max. 0.2 Nm  | 24560-141 | – | 24560-141 |
| ESD clip, PU 50 pieces | 24560-255 | | 24560-255 |

1) SPQ (standard pack quantity): Part number includes 1 piece, but delivery is exclusively made in standard pack quantity (SPQ); please order at least the SPQ quantity or a multiple

2) Part no. includes one packing unit (PU); delivery is exclusively made in PU

Subracks – EuropacPRO Rugged

ADAPTOR TO ACCOMMODATE CONDUCTION COOLED ASSEMBLIES (CCA)


ORDER INFORMATION

| | | | Adaptor to accommodate conduction cooled assemblies (CCA) in subracks | |
|--------------------|--|--|---|-------------------------|
| | | |  | |
| | | | <p>Al die-cast, silver, can be screw-fixed, 0.8" pitch; suitable for heavy and rugged horizontal rails, incl. fixing material kit</p> | |
| Board length mm | | | VPX PU 1 pair | CompactPCI PU 1 pair |
| 160 | | | 24566-004 | 24566-005 |


2) Part no. includes one packing unit (PU); delivery is exclusively made in PU

GUIDE RAILS FOR PLUG-IN UNITS AND FRAME TYPE PLUG-IN UNITS, ONE-PIECE, GROOVE WIDTH 2 MM AND 2.5 MM

ORDER INFORMATION

| | | | For plug-in units and frame type plug-in units "Standard" | |
|---|--------------------|--------------|---|--------------------------------|
| <p>Assembly Plastic guide rail - can be clipped into Al extruded horizontal rails - can be clipped into 1.5 mm thick plates</p> <p>Storage temperature from -40 °C ... 130 °C</p> | | |  | |
| | | | <p>up to 220 mm length, PBT, UL 94 V-0; from 280 mm length, multi-piece, end piece PBT, UL 94 V-0, central section Al extrusion</p> | |
| Board length mm | Groove width mm | Colour mm | PU 10 pieces ²⁾ | 1 piece (SPQ 50) ¹⁾ |
| 70 | 2 | red | – | 34579-230 |
| 70 | 2 | grey | – | 34579-231 |
| 160 | 2 | red | 24560-351 | 64560-001 |
| 220 | 2 | red | 24560-353 | 64560-002 |
| 280 | 2 | red | 24560-379 | – |
| 340 | 2 | red | 24560-380 | – |
| 160 | 2.5 | red | – | 64560-096 |
| 220 | 2.5 | red | – | 64560-098 |

Accessories

| | | | |
|--|---|------------------|------------------|
| Retention screw, PU 100 pieces; Torque max. 0.2 Nm |  | 24560-141 | 24560-141 |
| ESD clip, PU 50 pieces | | 24560-255 | 24560-255 |

1) SPQ (standard pack quantity): Part number includes 1 piece, but delivery is exclusively made in standard pack quantity (SPQ); please order at least the SPQ quantity or a multiple

2) Part no. includes one packing unit (PU); delivery is exclusively made in PU

Description of accessories see from page 6.107